

BIG-STICK OUTSIDE

DESCRIPTION (Speed, Perfection and Longevity)	Patented PVC tight fibered cotton composite corner tape that is 3" wide nominal, .026" thick using a PUR hot melt down the center fold. Big-Stick Outside is available in 8', 9', 10'; lengths and custom lengths are also available. Strait-Flex Big-Stick Outside is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.
ADVANTAGES	<ul style="list-style-type: none"> • No callbacks on outside 90-degree corners due to cracking or denting • Big Stick creates a fast, perfect, outside corner that can be installed by an apprentice • Damage proof design • Withstands settling, lumber shrinkage and temperature variation • Faster hanging and finishing time (guarantee) • Will not shrink, blister, tear or wrinkle • Installation does not require fasteners, stapling, or any special tools • Can run through hopper to mud both sides • Material can be second coated immediately • Material will not fuzz-up during sanding • Water resistant, rustproof • Saves 25-50% on installation time
WARRANTY	Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Contact Strait-Flex International Inc for complete details.
DIRECTIONS	<ul style="list-style-type: none"> • Apply using liberal coat of all-purpose compound to corner or angle with joint knife. Big Stick can also be put through a hopper to mud both sides. • Press Big Stick into wet compound, adjust if necessary to create straight line and remove excess compound. • Apply second coat of compound "immediately", lightly skim coat surface of Big Stick. • Apply final coat if required, same as second coat and let dry. Sand lightly to smooth surface. • Big Stick will not fuzz up during sanding. Painted surface of Big Stick must be thoroughly dry before applying second paint coat.
STORAGE	Store in dry place protected from moisture

Submittal Approvals:

Job Name:	
Contractor:	Date: